



Prevent Mold

On The Surface of The Coating on Construction Materials After Remediation

MycoDyne™ is a specialty product for the remediation and restoration industry developed from a proprietary combination of technologies. Once applied to remediated or restored surfaces, MycoDyne™ will provide long-term protection against mold and mildew, by prohibiting growth on the surface the coating for the functional life of that surface.

MycoDyne™ offers remediation and restoration contractors the ability to deliver greater value to their customers by having a highly effective coating solution for immediate and long-term protection against the recurrence of mold; by preventing growth on the surface of the coating .

MycoDyne™ is so effective that customers and contractors benefit from peace of mind that all treated surfaces are covered by a 25-year product liability warranty.



PROVIDED WITH A 25 YEAR WARRANTY

MycoDyne™ will protect the coating surface of materials like:

- Framing (wood & steel)
- Concrete Floors & Basements
- Concrete Block
- Sheetrock Backing*
- Floor Joists
- Trusses
- OSB
- Plywood
- Wall Panels

Put MycoDyne™ to the Test

MycoDyne™ is an easy-to-apply formula combining the capabilities of long-lasting inorganic technology and super-effective, liquid-based solutions to create the perfect protective coating. In lab-tests, MycoDyne™ eliminates over 99% of mold on the surface of the coating on treated construction materials and continues to prevent mold for many years to come.

So Easy to Use

Remediation and restoration contractors benefit from MycoDyne™'s easy spray-on application to protect the coated surfaces in one easy step. Once restoration and clean-up is completed apply the MycoDyne™ coating, allow to dry, and recurring mold problems are eliminated on the surface of the coating . MycoDyne™ it's fast-drying, and will not impede construction deadlines!

*MycoDyne coating is a surface coating solution, growth beneath the coating on sheetrock in the gypsum and paper layer may occur



Technical Data

In numerous accelerated lab tests, MycoDyne™ has demonstrated on the surface of the coating to provide both immediate performance in eliminating mold as well as longevity--the hallmarks of the proprietary formula. In these tests conducted at several different independent labs across the country using industry accepted protocols, MycoDyne™ has demonstrated its ability to eliminate mold on the surface of the coating, as well as inhibit more than 99% of mold growth after application--for virtual elimination of mold.

Additional studies have demonstrated that MycoDyne™ will remain effective for up to 70 years, based on release rates.

Representative Mold Growth Results

Sample Label	Contact Test	Accelerated Aging Test
MycoDyne™ Treated Sample	No Growth	No Growth
Control Sample	26	142

Results represent CFU/cm

Application Specifics

- 1 All surfaces must be free of debris, oil, grease or anything that would prevent direct contact of MycoDyne™ to the intended surface.
- 2 MycoDyne™ must be mixed thoroughly prior to and during application. Do not dilute.
- 3 Cover nearby surfaces such as window frames, doors, fixtures, etc., with masking materials prior to application of MycoDyne™ as needed.
- 4 Apply MycoDyne™ as specified by the Application Technical Data Sheet and allow to dry for at least 20 minutes.